

# #24L Clevis Hanger Extended


**Finishes** Zinc Plated, Bare Metal, Hot Dipped Galvanized, Epoxy

**Materials** Carbon Steel, Stainless Steel 304SS & 316SS

**Approvals** Complies with MSS SP-58 and SP-69 (Type 1).

**Recommended** Recommended for the suspension of non-insulated stationary pipe lines allowing for vertical adjustment.

Maximum temperatures: Bare Metal 650°F  
Galvanized & Epoxy 450°F



'B'  
Rod Take-Out  
Pipe center to bottom of hanger rod.  
'C'  
Pipe center to top of hanger.  
'D'  
Bottom of pipe to top of hanger

MODIFIED HANGERS ARE REQUIRED FOR INSULATION THICKER THAN THAT SHOWN IN THE SPECIFICATION DATA TABLE

| IRON PIPE SIZE | SPECIFICATION DATA |        |        |         | MAX. INSULATION THK. | REC. MAX LOAD (LBS.) | APP'X WT. PER 100 (LBS) | PC'S PER PKG. |
|----------------|--------------------|--------|--------|---------|----------------------|----------------------|-------------------------|---------------|
|                | A                  | B      | C      | D       |                      |                      |                         |               |
| 3/4            | 3/8                | 2 7/8  | 3 5/8  | 4 1/4   | 2"                   | 730                  | 50                      | 50            |
| 1              | 3/8                | 3 1/4  | 4      | 4 11/16 | 2"                   | 730                  | 57                      | 50            |
| 1 1/4          | 3/8                | 3 5/8  | 4 7/16 | 5 1/4   | 2"                   | 730                  | 63                      | 50            |
| 1 1/2          | 3/8                | 4 1/16 | 4 3/4  | 5 3/4   | 2"                   | 730                  | 71                      | 25            |
| 2              | 3/8                | 6 1/2  | 7 7/16 | 8 11/16 | 4"                   | 730                  | 84                      | 25            |
| 2 1/2          | 1/2                | 7 1/2  | 8 7/16 | 9 15/16 | 4"                   | 1350                 | 189                     | 25            |
| 3              | 1/2                | 7 9/16 | 8 5/8  | 10 5/16 | 4"                   | 1350                 | 199                     | 20            |
| 4              | 5/8                | 8 3/16 | 9 3/8  | 11 5/8  | 4"                   | 1430                 | 245                     | 10            |
| 5              | 5/8                | 8 3/4  | 9 7/8  | 12 5/8  | 4"                   | 1430                 | 298                     | 10            |
| 6              | 3/4                | 9 3/8  | 10 5/8 | 14      | 4"                   | 1940                 | 336                     | 10            |
| 8              | 3/4                | 11     | 12 3/8 | 16 3/4  | 4"                   | 2000                 | 670                     | 10            |
| 10             | 7/8                | 12 1/4 | 13 3/4 | 19 3/16 | 4"                   | 3600                 | 1100                    | BULK          |
| 12             | 7/8                | 13 5/8 | 15 1/8 | 21 9/16 | 4"                   | 3800                 | 1380                    | BULK          |

QWI 4.3.1 Issue Date Nov/21 Rev.9

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at [www.taylorwalraven.ca](http://www.taylorwalraven.ca)

For more information, please contact Customer Service at 1-800-263-8652