

#525 Pipe Saddle Support C/W U-Bolt

Finish Bare Metal, Hot Dipped Galvanized

Material Carbon Steel, Stainless 304SS & 316SS

Approvals Complies with Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type 36, 37)


Recommended 3" through 36"

Designed to be used in conjuction with a base stand to support pipe running close to the floor. U-Bolt secures pipe to saddle. Specify pipe size, figure number, name and finish.

Base stand ordered separately. Requires accurate center line of pipe to floor dimension "L".

Welded Gussets on 8" and up





	SPECIFICATION DATA		WGT.
PIPE SIZE			EACH
	PIPE SIZE A	В	(LBS.)
3	3	3 3/4	6.00
4	3	4 3/16	6.72
5	3	4 13/16	7.30
6	3	5 7/16	11.06
8	3	6 15/16	14.30
10	3	8 7/16	18.53
12	3	9 15/16	23.92
14	4	10 15/16	39.10
16	4	12 3/8	44.47
18	4	13 7/8	52.95
20	6	15 3/8	84.72
24	6	17 15/16	100.00
30	6	21 5/16	113.10
36	8	24 1/2	163.74

QWI 4.3.1 Issue Date Dec/23 Rev.8