


#57 Machine Threaded Rod
- Right-hand Threads

#58 Machine Threaded Rod
- Right and Left-hand Threads

Finishes Bare Metal, Zinc Plated, Hot Dipped Galvanized*

Materials Carbon Steel, Stainless Steel 304SS & 316SS

Recommended *The acceptability of galvanized coating at temperatures above 450°F is at the discretion of the end user.



3/8"-4" Diameter: UNC-2A CLASS fit.

ROD SIZE A	Threads per Inch	Max. Load		Standard Rod Thread Length D
		650° F	750° F	
3/8	16	730	572	2 1/2
1/2	13	1350	1057	2 1/2
5/8	11	2160	1692	2 1/2
3/4	10	3230	2530	3
7/8	9	4480	3508	3 1/2
1	8	5900	4620	4
1 1/4	7	9500	7440	5
1 1/2	6	13800	10807	6
1 3/4	5	18600	14566	7
2	4 1/2	24600	19265	8
2 1/4	4 1/2	32300	25295	9
2 1/2	4	39800	31169	10
2 3/4	4	49400	38687	11
3	4	60100	47066	12
3 1/4	4	71900	56307	13
3 1/2	4	84700	66331	14
3 3/4	4	98500	77139	15
4	4	113400	88807	15
4 1/4	4 UN	129400	101337	18
4 1/2	4 UN	146600	114807	18
4 3/4	4 UN	164700	128982	18
5	4 UN	184000	144096	18

QWI 4.3.1 Issue Date Nov/21 Rev.4

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at www.taylorwalraven.ca

For more information, please contact Customer Service at 1-800-263-8652