

#66 Welded Beam Attachment #67 Welded Beam Attachment - Without Hardware



Finishes Bare Metal, Zinc Plated, Hot Dipped Galvanized


Materials Carbon Steel, Stainless Steel 304SS & 316SS

Approvals Complies with MSS SP-58 and SP-69 (Type 22).


Recommended For attachment to bottom of beams where heavier loads are being supported.

Maximum temperatures: Bare Metal 750°F, Galvanized 450°F

Note #67 available up to 1 3/4"



2" Rod Dia. and Larger are Fabricated.



1 3/4" Rod Dia. and Smaller are Formed using Bolt or Pin.

ROD SIZE A	SPECIFICATION DATA						RECOM. LOAD 650°F	RECOM. LOAD 750°F	BOLT or PIN SIZE	APP'X WT. PER 100 (LBS)
	E *	B	H	R	S	T				
3/8	2	2	9/16	7/8	1 1/4	1/4	730	572	1/2 x 2 1/2	117
1/2	2	2	11/16	7/8	1 1/4	1/4	1350	1057	5/8 x 2 3/4	131
5/8	2	2	13/16	7/8	1 1/4	1/4	2160	1692	3/4 x 2 3/4	155
3/4	2	2 1/2	15/16	1 1/8	1 7/8	3/8	3230	2530	7/8 x 4	279
7/8	3	2 1/2	1 1/8	1 1/4	2	3/8	4480	3508	1 x 4	394
1	3	3	1 1/4	1 1/2	2 3/4	1/2	5900	4620	1 1/8 x 5	629
1 1/4	3	4	1 1/2	2	3	5/8	9500	7440	1 3/8 x 6 1/2	1022
1 1/2	4	5	1 3/4	2 1/2	3 1/2	3/4	13800	10807	1 5/8 x 6 1/2	1902
1 3/4	5	5	2	2 3/4	3 3/4	3/4	18600	14566	1 7/8 x 6 7/8	2418
2	5	6	2 3/8	3 1/4	3 1/2	1/2	24600	19265	2 1/4 x 6 7/8	3055
2 1/4	5 3/4	6	2 5/8	3 1/2	3 1/2	5/8	32300	25295	2 1/2 x 7 3/8	3678
2 1/2	5 3/4	6	2 7/8	3 3/4	3 3/4	5/8	39800	31169	2 3/4 x 7 5/8	3970
2 3/4	5 3/4	6	3 1/8	4	3 3/4	5/8	49400	38687	3 x 7	4080
3	6 1/4	7	3 3/8	4	3 3/4	5/8	60100	47066	3 1/4 x 7	4670
3 1/4	7	7	3 5/8	4 1/2	4 1/4	3/4	71900	56307	3 1/2 x 7 3/4	6210
3 1/2	7 1/2	8	3 7/8	4 1/2	4 1/4	3/4	84700	66331	3 3/4 x 7 3/4	7240

QWI 4.3.1 Issue Date Nov/21 Rev.9

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at www.taylorwalraven.ca

For more information, please contact Customer Service at 1-800-263-8652