

#70 Protection Saddle 1" Insulation

Finishes Bare Metal, Zinc Plated, Hot Dipped Galvanized


Materials Carbon Steel, Stainless Steel 304SS

Approvals Complies with MSS SP-58 and MSS SP-69 (Type 39)

Recommended Designed to protect pipe insulation from crushing, typically used on high temperature pipe lines.

Maximum temperatures: Carbon Steel 650°F, Alloy 950°F

Notes All saddles 12" in length.
Center rib starts at 12" IP
C & D dimensions to not apply to #94S



IRON PIPE SIZE	SPECIFICATION DATA					ACTUAL THICKNESS OF COVERING	RECOM. MAX. LOAD (LBS.)	APP'X WT. PER 100 (LBS.)
	C	D	HANGER ROLLER SIZE					
			# 94/95	# 93	#94S			
3/4	1 9/16	1 15/16	2	2 1/2	2 - 3-1/2	7/8	1200	146
1	1 13/16	2 1/4	2 1/2	3	2 - 3-1/2	1 1/16	1200	146
1 1/4	1 15/16	2 1/2	2 1/2	3	2 - 3-1/2	15/16	1200	146
1 1/2	2 1/8	2 5/8	3	3 1/2	2 - 3-1/2	1 1/16	1200	150
2	2 7/16	3	3 1/2	4	2 - 3-1/2	1 1/16	1200	155
2 1/2	2 11/16	3 1/4	3 1/2	5	2 - 3-1/2	1 1/16	1200	155
3	2 15/16	3 1/2	4	5	2 - 3-1/2	1	1200	178
3 1/2	3 7/16	4	5	6	4 - 6	1 5/16	1200	199
4	3 9/16	4 3/16	5	6	4 - 6	1 1/16	1200	199
5	4 1/8	4 13/16	6	8	4 - 6	1	1200	199
6	4 9/16	5 3/8	8	8	4 - 6	15/16	1800	394
8	5 9/16	6 9/16	10	12	-	1 1/16	1800	478
10	6 5/8	8	12	14	-	1	1800	478
12	7 5/8	8 7/8	14	16	-	1 1/8	5000	750
14	8 11/16	10 1/16	16	18	-	2	5000	750

Shaded rows indicate common saddle size.

QWI 4.3.1 Issue Date May/25 Rev.12

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at www.taylorwalraven.ca

For more information, please contact Customer Service at 1-800-263-8652