

#75 Protection Saddle 4" Insulation

Finishes Bare Metal, Zinc Plated, Hot Dipped Galvanized


Materials Carbon Steel, Stainless Steel 304SS

Approvals Complies with MSS SP-58 and MSS SP-69 (Type 39)

Recommended Designed to protect pipe insulation from crushing, typically used on high temperature pipe lines.

Maximum temperatures: Carbon Steel 650°F, Alloy 950°F

Notes All saddles 12" in length.
Center rib starts at 12" IP



IRON PIPE SIZE	SPECIFICATION DATA				ACTUAL THICKNESS OF COVERING	RECOM. MAX. LOAD (LBS.)	APP'X WT. PER 100 (LBS.)
	C	D	HANGER ROLLER SIZE				
			# 94/95	# 93			
4	6 9/16	7 11/16	12	14	4 1/8	1800	624
5	7 3/16	8 1/4	12	14	4 3/16	1800	624
6	7 5/8	9 1/8	14	16	4 1/8	1800	1001
8	8 11/16	10 1/8	16	18	4 1/8	1800	1001
10	9 11/16	11 5/16	18	20	4 1/16	1800	1097
12	10 13/16	12 3/8	20	24	4 1/16	5000	1485
14	11 7/16	13 1/8	20	24	3 15/16	5000	1485
16	12 5/16	14 3/16	24	--	4	7200	1564
18	13 1/2	15 7/16	24	--	4	7200	1628
20	14 3/16	16 5/8	30	--	4	7200	1692

Shaded rows indicate common saddle size.

QWI 4.3.1 Issue Date May/25 Rev.11

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at www.taylorwalraven.ca