

#77 Protection Saddle 4 1/2" Insulation

Finishes Bare Metal, Zinc Plated, Hot Dipped Galvanized


Materials Carbon Steel, Stainless Steel 304SS

Approvals Complies with MSS SP-58 and MSS SP-69 (Type 39)

Recommended Designed to protect pipe insulation from crushing, typically used on high temperature pipe lines.

Maximum temperatures: Carbon Steel 650°F, Alloy 950°F

Notes All saddles 12" in length.
Center rib starts at 12" IP



IRON PIPE SIZE	SPECIFICATION DATA				ACTUAL THICKNESS OF COVERING	RECOM. MAX. LOAD (LBS.)	APP'X WT. PER 100 (LBS.)
	C	D	HANGER ROLLER SIZE				
			# 94/95	# 93			
2	5 13/16	6 13/16	12	12	4 1/2	1800	596
2 1/2	6 1/8	7 1/8	12	12	4 1/2	1800	596
3	6 7/16	7 7/16	12	12	4 1/2	1800	596
4	7 1/16	8 3/16	14	14	4 1/2	1800	667
5	7 11/16	8 3/4	16	16	4 1/2	1800	667
6	8 1/8	9 5/8	16	16	4 1/2	1800	1064
8	9 3/16	10 5/8	18	18	4 1/2	1800	1064
10	10 3/16	11 13/16	20	20	4 1/2	1800	1160
12	11 5/16	12 7/8	24	24	4 1/2	5000	1581
14	11 15/16	13 5/8	24	24	4 1/2	5000	1581
16	12 13/16	14 11/16	24	--	4 1/2	7200	1660
18	14	15 15/16	30	--	4 1/2	7200	1724
20	14 11/16	17 1/8	30	--	4 1/2	7200	1788

QWI 4.3.1 Issue Date Mar/22 Rev.4

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at www.taylorwalraven.ca

For more information, please contact Customer Service at 1-800-263-8652