

910R Rigid Strut Clamp

Finish Zinc Plated, Hot Dipped Galvanized

Material Carbon Steel, Stainless Steel 316SS

Recommended 2-Piece Strut Pipe Clamp (Rigid / IPS) used to secure pipe or conduit to strut channel.

Note Stainless Steel 910R 2" to 910R 8" = 14 GA.
Zinc Plated c/w zinc plated headscrew and nut.
Hot Dipped Galvanized c/w stainless headscrew and nut.



PART NUMBER	SPECIFICATION DATA			REC MAX LOAD (LBS)	APP'X WT PER PKG. (LBS)	PC'S PER PKG.
	IRON PIPE SIZE	OD	GAUGE			
910R 3/8	3/8	0.675	16	400	0.12	1
910R 1/2	1/2	0.840	16	400	11	100
910R 3/4	3/4	1.050	14	600	15	100
910R 1	1	1.315	14	600	18	100
910R 1 1/4	1 1/4	1.660	14	600	19	100
910R 1 1/2	1 1/2	1.900	14	600	22	100
910R 2	2	2.375	14	600	13	50
910R 2 1/2	2 1/2	2.875	12	800	10	25
910R 3	3	3.500	12	800	11	25
910R 3 1/2	3 1/2	4.000	12	800	13	25
910R 4	4	4.500	12	800	14	25
910R 5	5	5.563	12	800	13	20
910R 6	6	6.625	12	800	18	25
910R 8	8	8.625	12	800	24	25
910R 10	10	10.75	12	800	1	1
910R 12	12	12.75	12	800	1.5	1
910R 14	14	14	12	800	2	1
910R 16	16	16	12	800	3	1

QWI 4.3.1 Issue Date Jul/25 Rev.3

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at

www.taylorwalraven.ca

For more information, please contact Customer Service at 1-800-263-8652